

SAMSUNG

T H E R M A L R E C E I P T P R I N T E R



SRP-350

Thermal Receipt Printer

Best Thermal Receipt Printer SRP-350 completely satisfy you with versatile functions such as fast printing speed, compact size, easy paper supply D & P (Drop and Print) at any store environment.

Specially USB Interface help you connect the recent PC POS terminal. And If you want to change interface, you can set other interface easily without buying new printer (Modular I/F design).

SRP-350

Thermal Receipt Printer

• Dimension



• D & P(Drop and Print) Paper Supply



• Back Side



- Serial Interface
- Drawer Kick-out
- Power Jack

- **Fastest Printing Speed (150mm / sec, 47.2 LPS)**
- **Multiple Interface (RS-232C, RS-485, USB, IEEE-1284) Modular Interface Card**
- **Saves Install Space (Compact Size, Wall-Mount)**
- **Easy-to-use**
 - D & P (Drop and Print) paper supply
 - Simple to eliminate Paper Jam
 - Complete Compatibility

■ Specifications

| | | SRP-350 |
|---------------------------------|----------------------------|--|
| PRINT | Printing Method | Direct Thermal |
| | Printing Speed | 132 mm / sec |
| | Dot Density | 180 dpi (7 dot / mm) |
| | Printing Direction | Unidirectional with friction feed |
| | Character per Line | Font A : 42 |
| | | Font B : 56 |
| PAPER SPECIFICATION | Paper Type | Thermal Paper |
| | Paper width | 79.5 ±0.5 mm |
| | Paper Roll Diameter | Max. Ø 83.0 mm |
| PAPER SUPPLY METHOD | | D & P (Drop and Print) Mechanism |
| RELIABILITY | MCBF | 37,000,000 Lines |
| | TPH Life | 1 x 10 ⁸ pulse, 100 km |
| CHARACTER SET | | Alphanumeric Character : 95 |
| | | Extended Graphic : 128 x 7 page (1 space page) |
| | | International character : 32 |
| BARCODE | | EAN-13, EAN-8, CODE 39, CODE 93, CODE 128, ITF, CODE BAR, UPC-A, UPC-E |
| EMULATION | | TM-88 (■), TSP552 (■) |
| DRIVER | | DOS, Windows 3.1 / 95 / 98 / NT |
| SENSOR | | Near end sensor, Paper end sensor |
| DRAWER PORT | | 2 port |
| INTERFACE | | RS-232C (Standard) |
| OPTION I / F CARD | | RS-232C, RS-485, USB, IEEE-1284 |
| POWER SUPPLY | | AC 120V ~ 230V ± 10% (Adapter) |
| DIMENSION (W X L X H mm) | | 145 x 195 x 146 |
| AUTO CUTTER | Type | Guillotine |
| | Life | 500,000 cuts |

■ Options

WM-350
Wall Mount Bracket



* Design and specifications are subject to change without notice.



HEAD OFFICE (SEOUL, KOREA)

8th FL, Samsung Main Bldg, 250, 2-Ka
Taeyung-Ro, Chung-Ku Seoul, Korea 100-742
TEL: +82 2 751 2785, 2790 FAX: +82 2 751 2690
Internet Homepage : <http://samsungelectronics.com>

Distributed by:

SAMSUNG

SRP350

COMPARISON

| Item | SRP-300(SAMSUNG) | SRP-350(SAMSUNG) | TM-T88 II(EPSON) |
|--------------------------|---------------------|-------------------------------|-------------------------|
| Print Method | direct line thermal | direct line thermal | direct line thermal |
| Print Speed & Resolution | 73.3mm/sec(180dpi) | 150mm/sec(180dpi) | 120mm/sec(180dpi) |
| Paper Width | 80mm | 80mm | 80mm |
| Print Columns | 42 / 56 | 42 / 56 | 42 / 56 |
| Reliability | Mecha | 10M Lines | 37M Lines |
| | TPH | 50km | 100km |
| | Autocutter | 0.3M Cuts | 1M Cuts |
| Interface | RS-232C, Parallel | RS-232C/485 IEEE-1284, USB | RS-232C/485 Parallel |
| Dimension(W*L*Hmm) | 144 * 214 * 138 | 145 * 194 * 146 | 145 * 195 * 148 |
| Paper Handling | - | Drop & Print | Drop-In-Roll Paper |
| Drawer Port | 2 | 2 | 2 |